

# Caulking

## GEOCEL 2300® TRIPOLYMER SEALANT



- Will not crack
- Asphalt compatible
- Exceptional elongation and flexibility
- Excellent adhesion to all building surfaces, even when damp
- Superior ultraviolet resistance
- Resealable – may be applied over itself
- Paintable
- No dirt pickup
- Easily applied, non-stringing formulation
- Available in Crystal Clear, standard colors and precision matched metal roof colors
- Mildew resistant
- CARB and VOC compliant

## GEOCEL 2300SWD™ TRIPOLYMER SEALANT



- Precision matched colors available for siding, windows, and doors
- Excellent adhesion to aluminum, steel, vinyl, fiber cement, wood, masonry and concrete
- Adheres in wet or damp conditions
- Ultraviolet resistant
- Paintable – contains no silicone
- Water-repellent cartridge wrap
- Cold temperature application
- No primer required
- Resists dirt pick-up
- Mildew resistant
- Resealable – may be applied over itself
- Permanently flexible
- ASTM C920 compliant
- VOC compliant in all 50 states

## GEOCEL 2320/2321® GUTTER AND NARROW SEAM SEALANT



- Excellent adhesion to most building surfaces, even when wet or oily
- Superior ultraviolet resistance
- All temperature application
- Paintable
- Semi-self-leveling
- Cleans up easily
- Asphalt compatible
- CARB and VOC compliant

## GEOCEL 3300® POLYURETHANE ROOFING SEALANT



- Miami-Dade county product approved for hurricane-tough adhesion
- Permanently flexible
- Minimal shrinkage
- Meets TT-S-00230C, ASTM C920-87
- Low odor, low VOC
- Non-corrosive, non-sag
- Roofing applications: clay tile, concrete tile, metal, kynar coated metal, composition shingles

## GEOCEL 4500EPDM™ SCYPOLYMER™ ADHESIVE/SEALANT



- Lap adhesive or scrim edge sealant for black EPDM roofing membranes
- Applies, adheres & cures underwater
- No primers or cleaners needed
- May be used with EPDM seam tapes, flashing or patches
- Adheres to most common roofing substrates
- Safe, non-solvent formula
- Meets LEED and NAHB guidelines
- VOC compliant in all 50 states

**Geocel®**

## OSI® QUAD® — ADVANCED FORMULA SEALANT



Developed for Vinyl Siding, Windows, Wood & Fiber Cement

- Excellent primerless adhesion
- Paintable
- Long Lasting
- Permanently Flexible
- Clear is crystal clear
- VOC Compliant formula
- Custom color matching availability
- Over 250 colors and counting

## OSI® SBR-100™ WINDOW & SIDING CAULK



- First all-season formula; extrudes easily between 0° and 100° F
- No tooling required
- Never stringy
- Skins over in one hour
- Wide range of colors
- Paintable after curing
- SBR-100 White is available in a VOC Compliant formula

## OSI® VP-275™ MULTI-PURPOSE SILICONE SEALANT



- Neutral-cure, low modulus 100% silicone
- Primerless adhesion to porous and non-porous materials
- Permanently flexible
- Outstanding weatherability
- Solvent free & non-toxic
- Non-corrosive to metals

## OSI® HM-270™ CONSTRUCTION SILICONE SEALANT



- 100% Silicone
- Primerless adhesion to both porous and non-porous surfaces
- Outstanding weatherability
- Solvent free, non-toxic, neutral curing
- Non-corrosive to metals
- HM-270 can be used in VOC restricted areas

## OSI® PL™ WINDOW, DOOR & SIDING SEALANT



- 50 year life...the ultimate in high performance
- VOC compliant
- Resists weathering
- Paintable
- Permanently flexible
- Seal around windows, doors and utility penetrations

