



DEWALT 2 HP 4 GAL. TWIN STACK ELECTRIC COMPRESSOR

4 CFM at 100 PSI 4 gallon twin stack tank design with proven acceptance in the market.

D55153



DEWALT 6.5 HP 8 GAL. GAS WHEELED PORTABLE COMPRESSOR

9.0 SCFM Pump delivers the surge air power and recovery needed to run extra nailers over standard 8 gallon. DeWALT OHV engine with low oil shut off for engine protection. Long life cast iron pump prevents lock ups due to lack of lubrication. Low profile design allows for easy maneuverability.

D55672



DEWALT 6.5 HP GAS 10.5 GAL. COMPRESSOR

DeWALT (6.5 HP), OHV engine with low oil shut off for engine protection. Long life cast iron pump with exclusive low oil shut off device prevents lock ups due to lack of lubrication. One hand push/pull handle for ease of mobility on the job site. Roll cage and control panel provide protection to key compressor components.

D55684



HITACHI 2HP 4GAL TWIN STACK OIL LUBE ELECTRIC COMPRESSOR EC12

4.0 CFM at 90 PSI, direct drive electric motor, line regulator with gauge, O-ring on drain-cock, 2 gallon twin tanks, all metal inner construction and fan, oil lubricated pump.

HITEC12



HITACHI 5.5HP 8GAL WHEELBARROW GAS COMPRESSOR EC2510E

Solid cast iron cylinder, baseplate integrated control panel, pneumatic throttle control, full-size 3/8" locking regular.

HITEC2510E



DEWALT 1 QT. SYNTHETIC COMPRESSOR OIL

D55001 (NOT SHOWN)

BOSTITCH 1.5HP 1.6GAL OIL FREE ELECTRIC COMPRESSOR CAP1516

High efficiency 1.5 Peak HP draws only 8 amps. Weighs only 19.5lbs for maximum portability. Ultra-quiet operation for use in confined work spaces. High output oil-free pump requires no maintenance. Internal 1.6-gallon reserve air tank.

BOSCAP1516



BOSTITCH 2HP 6GAL OIL FREE PANCAKE ELECTRIC COMPRESSOR CAP2060P

Powerful 2 Peak HP industrial induction motor with manual reset overload protection draws only 10.5 amps. High output oil-free pump requires no maintenance. Cold weather start assist system and synthetic pump oil for fast easy startup.

BOSCAP2060



BOSTITCH 2.5HP 6GAL OIL LUBRICATED PANCAKE ELECTRIC COMPRESSOR CAP2560OL

Powerful 2.5 Peak HP 15 amp industrial induction motor with manual reset overload protection. High output oil-lubricated pump with cast iron cylinder for maximum life. Cold weather start assist system and synthetic pump oil for fast easy startup.

BOSCAP2560OL



DEWALT 3000 WATT GAS GENERATOR

DeWALT 196cc (6.5HP) OHV engine provides worksite reliability, 20% more starting watts than generators in its class. Maintenance free, brushless alternator, high amp surge capacity, dual breaker system, panel protection bars, large all metal gas tank, idle control, low oil shut off, super quiet muffler with spark arrester.

DG3000



DEWALT 4400 WATT GAS GENERATOR WITH BATTERY START

DeWALT 18 volt battery start. Battery and charger come with the generator. DeWALT 270cc (9hp) OHV engine provides worksite reliability, 20% more starting watts than generators in its class.

DG4400B



DEWALT 6300 WATT GAS GENERATOR WITH BATTERY START

DeWALT 18 volt battery start. Battery and charger come with the generator. DeWALT 389cc (13hp) OHV engine provides worksite reliability, 20% more starting watts than generators in its class.

DG6300B



DEWALT 7000 WATT GAS GENERATOR WITH BATTERY START

DeWALT 18 volt battery start. Battery and charger come with the generator. DeWALT 389cc (13hp) OHV engine provides worksite reliability, 20% more starting watts than generators in its class.

DG7000B



PORTER-CABLE 5500 WATT RATED GAS GENERATOR

Briggs and Stratton Vanguard Premium Engine. 5,500 Rated Watts, 8,850 Surge Watts. 7 gallon gas tank for long run times between fueling: 10.4 hours at 1/2 load and 7.0 hours at full load.

PCBSV550W



PORTER-CABLE 7,500 WATT GENERATOR

Briggs and Stratton Vanguard Premium Engine. 7,500 watts continuous, 10,750 watts surge, 13 HP Briggs & Stratton Vanguard engine, 7 gallon fuel tank, Semi-pneumatic wheels and full width axle are rugged enough to move over job-site debris easily.

PCBSV750W



SIEVERT®



PORTER-CABLE 3500 WATT GAS GENERATOR

Advanced, brushless alternator design. 6.5 Honda GX200 OHV engine: Compression release for easy recoil start, Cast-iron cylinder sleeve, Low oil protection. 4 gallon fuel tank provides 11.6 hours of run time at 1/2 load and 7.8 hours at full load.

PCCH350IS



PORTER-CABLE 4500 WATT GAS GENERATOR

Advanced, brushless alternator design. 9 HP Honda GX270 OHV engine: Compression release for easy recoil start, Cast-iron cylinder sleeve, Low oil protection. 7 gallon fuel tank provides 13.4 hours of run time at 1/2 load and 8.7 hours at full load.

PCH450IS-W



PORTER-CABLE 10,000 20HP HONDA ENGINE GENERATOR

Advanced, brushless alternator design. 20 HP Honda GX620 twin cylinder OHV engine: Electric start (12 volt 450 CCA battery included), Cast-iron cylinder sleeves, Low oil protection, Pressure lubrication and spin-on oil filter. 7 gallon fuel tank. Portability kit with 13" pneumatic tires included. Rugged all-metal construction, Ball bearings, Rubber isolators. Circuit breaker protection. Idle control. Hour meter. Fuel gauge. Lift kit.

PCH1000ISW



SIEVERT HEAVY DUTY PRO GENERATOR G21000

Features 20 HP electric start Honda GX620 engine. 12,000W max, 10,200W continuous output. Advanced brushless alternator with THD less than 6%. Engine and circuit breaker protection system. 8 gallon fuel tank. Heavy duty frame, wheel kit, sky hook, volt meter, hour meter, and more.

PRIG12000

