



A




B



E



F



G



H



A JOINT

Splices poles easily and securely with 6 ft. sections to achieve total desired height. Three separate safety stops. Works well with all pole lengths.

AP6J

B ALUM-A-POLE

All weather structural aluminum and Saf-T-Grip rubber exceeds OSHA standards. Poles can be spliced to 50' maximum shoulder working length. Lifetime non-slip, non-wear replacement warranty.

6' Pole – **AP6P**

12' Pole – **AP12P**

18' Pole – **AP18P**

24' Pole – **AP24P**

C END RAIL NET SYSTEM 14"

Protects materials or users from falling

APSER

D SAF-T-NET 22'

Falling to the ground scaffolding hazards are virtually eliminated because Saf-T-Net moves up and down with the worker.

APSNET

E SCAFFOLDING

5-1/4" rail 500 lb. rating. An infinitely joinable, non-overlapping walkway. Accepts Pro-Jack Saf-T-Lok Chain for protection from twist-out and upending. Designed for superior strength and traction. Large drain holes for rain and snow. Exclusive design provides minimal ice build-up

14" x 16' – **APSCAFF1416**

14" x 24' – **APSCAFF1424**

20" x 14' – **APSCAFF2014**

20" x 20' – **APSCAFF2020**

20" x 24' – **APSCAFF2024**

24" x 24' – **APSCAFF2424**

F BRACE

Folding model secures scaffolding to structure quickly and easily. Multi-angle swivel provides flexibility for mid-bracing on total structure. Universal joint fits any roof.

Foldable – **APBRAFF**

Rigid – **APBRAR** (NOT SHOWN)

G PRO-JACK

4,000 lb. tested telescopic pump-jack with safety features and a self-storing Saf-T Crank handle. Built-in Saf-T-Lok Chain. Secures staging too.

APPROJ

H PRO-BENCH

A telescoping aluminum workbench and guard rail combination. Up to 27" wide staging capacity. Built-in Saf-T-Lok Chain. Provides anti-theft and greater safety.

APPROB